



Model:Jezi-66



<b>System</b>	WEB	three levels account and password (admin/guest/user), multi user management
	P2P	Free, Plug and Play, no port forwarding
	APP	Android: search IPCAM P in Google play for APP download iOS: search IPCAM P in Appstore for APP download.
	PC Client CMS	1,4,9,16,25,36 multi windows in center management system, recording and alarm
	System and browser	Microsoft Win98 SE/ME/2000/XP、 Vista、 Win 7, Internet Explorer 6.0/7.0/8.0/9.0/10, FireFox, Google , Safari
<b>Main chipset</b>	operation system	Linux
	DSP	Hisilicon 32Bit RSIC Embedded Processor
	Sensor	1/4" CMOS
	Memory	64M(DSP built-in)
	FLASH	16M
<b>Video</b>	Compression format	H.264
	Pixel	<b>1.0 Megapixel</b>
	Frame rate	50Hz: 1~20fps , 60Hz: 1~25fps
	Resulation	(1280*720),VGA(640*352),QVGA(320*176)
	Image adjustment	The hue, brightness, contrast, saturation and sharpness are adjustable
	LUX	0.4 Lux/F1.2
	SNR	>48DB
	Shutter	1/50s(1/60s) ~ 1/100,000 s
	Lens	M12/3.6mm F1.2 , angle of view 90 ° (Diagonal) 3X digital zoom,Standard: 3.6mm optional: 6mm
	WB&BLC	Auto

<b>Night vision</b>	IR	Φ5 8pcs LED lights, Wavelength 850nm , IR angle 90 °
	Distance	IR distance 10m, photoresistor sensitivity: 0~5 Lx
<b>Audio</b>	Talk	Two way audio
	Format	G711/726
	Speaker	1W, 8Ω
	Microphone	-52dB
<b>Structure</b>	Motor control	Built-in 2 motors
	IR-CUT	Auto switch , without color cast
	Pan & Tilt	Horizontal: 355°, Vertical: 120°
	Cruise	IE support auto cruise and 8 preset positions.
<b>Network</b>	Wire	RJ-45 10/100Mb
	Online limit	Up to 3 visitors oneline for the first stream, Up to 3 visitors online for the second stream, Total up to 6 visitors online.
	Support IP address	Static IP, Dynamic IP, PPPOE
	Protocal	Support TCP/IP、 HTTP、 ICMP、 DHCP、 FTP、 SMTP、 P PPoE and so on
<b>Wireless</b>	WIFI	WIFI IEEE 802.11B/G/N
	Antenna	2.4GHz 2dBi antenna
	Transmission rate	150Mbps (Max)
	Mode	AP mode, QR code
<b>Recording</b>	Type	TF card , support 24 hours / Motion Recording.
	Micro SD size	2G/4G/8G/16G/32G, 64G max.
	Format	AVI
	Protocal	Compatible with onvif 2.1
<b>Housing</b>	Material	Plastic (ABS)
	Network light	Yellow or green
<b>Power</b>	Power	DC5V 2A
	Frequency	50Hz / 60Hz

<b>Environment</b>	Assembly	Indoor
	Temperature	-10~50 °C
	Humidity	10% ~ 90% RH
<b>Packing</b>	Box	Color box and cartoon
	Dimension	Product size: 120*90*115mm (L*W*H) box size: 200*160*120mm (L*W*H) Cartoon size: 625*415*340mm (L*W*H)
	Weight	Net weight: 0.5kg , Gross weight (including box) : 0.65kg Carton Weight: 13kg (only for reference)
	Accessories	Power adapter, manual, screws, bracket, antenna
<b>Alarm</b>	Input/output	none
	Motion detection	Support 1 detection area for mobile and 4 areas for PC
	Alarm notification	Push notification for iPhone/Android APP Upload pictures to only one email address, three pictures to the max. Upload snapshot and alarm records to TF card (when insert Micro TF card) and FTP server
<b>Certificate</b>	Certificate	ISO FCC CE

date: 2015-7-8