

Model: Jezi-12B
Standalone Fingerprint System



Specifications

» User Capacity	1000
» Fingerprint	500
» Card	500
» PIN	500
» Operating Voltage	12V DC
» Idle Current	< 50 Ma
» Active Current	< 100 Ma
» Fingerprint Reader	Optical fingerprint Module
» Resolution	500 DPI
» Identification time	< 1S
» FAR	< 0.0001%
» FRR	< 0.01%
» Proximity Card Reader	Industry Standard 26 bit
» Radio Technology	125KHz Industry Proximity EM Card
» Read Range	1 ~ 5 cm
» PIN Reader	4~ 6 digits PIN
» Wiring Connections	Relay output, exit button, alarm, Wiegand output
» Communication	Door bell
» Relay	USB for downloading/uploading
» Adjustable Relay Output Time	One (NO, NC, Common)
» Lock Output Load	1 ~ 99 Seconds (5 seconds default)
» Alarm Output Load	2 Amp Maximum
» Wiegand Interface	5 Amp Maximum
» Environment	Wiegand 26 bits output
» Operating Temperature	-20°C ~ 50°C (50°F ~ 140°F)
» Operating Humidity	20% RH ~ 90% RH
» Physical	ABS Enclosure
» Dimensions	8.8L x 8.8W x 3.0H (cm)
» Unit Weight	350g
» Shipping Weight	400g



Fingerprint



Access Control



USB Disk



RFID Reader