



Support USB Flash Driver Download for the excel files of detailed temperature detection record and attendance report

Specifications

Product Model	Case Material	Plastic shell, Metal back plate
Appearance	CPU Processor	4 Core 1.2G
Temperature detection distance		0.5 meter;
Temperature detection error		0.5℃,
Temperature detection minimum unit		0.1℃
Firmware Specification	RAM	4G DDR3
	ROM	32G eMMC
	Camera	200W Pixel HD Colorful Camera
		100W Infrared Camera
	Fill Light	Highlight LED Fill Light
		Dual Infrared High Power Fill Light
	Display Screen	5.0 inch Electronic Capacity Touch Screen
	Screen Resolution	854*480
	Keypad	Touch Virtual Keypad
	Communication Method	TCP/IP,WIFI,USB PEN DRIVE
	FRR	≤ 0.1%
	FAR	≤ 0.001%
	Product Size	154mm*152mm*22mm
	Power Supply	DC 12V, 2A
	Working Temperature	− 15℃ to 60℃
	OS	LINUX System
	Language	Chinese, English and other languages(Customized)
	User ID Capacity	3000
	Face Capacity	3000
	User Record Capacity	1,000,000
	Identification Type	Dynamic Face Recognition, Password, Face Recognition& Password
	Face Recognition Mode	1:1, 1:N
	Identification Distance	Dynamic Distance 0.5 Meter