



Number of Chassis		1 Chassis	2 Chassis	3 Chassis	
Number of Universal Slot		4	8	12	
Number of CPU		1			
Total System Ports (Trunk + Extension)		222			
Total Legacy Ports (Trunk + Extension)	Total Legacy Ports (Trunk + Extension)	74	148	222	
	Trunks (Max.)	Analog	12	24	36
		ISDN BRI	16	32	48
		ISDN PRI (2M)	30	60	90
	Extensions (Max.)	Multi-line Terminals	24	48	72
		Analog Extensions	32	64	96
		DSS Console	3	6	9
		Doorphone		6	
IP	IP Trunks (SIP / H.323)		64		
	IP Extensions		112		
Audio / Others	Relay		11		
	Paging		3		
	External Music on Hold		1		
	BGM		1		
	Ethernet Port		1		
	Analog Modem		1		
Voice Response System/ Voice Mail (VRS/VM)	VRS/VM Storage	2 Hours (Built-in) / 15 Hours (By Small SD card) / 120 Hours (By Large SD card)			
	Voice Prompts for VRS/VM	1 Language (Built-in) / 26 Languages (By Small or Large SD card)			
VoIP	Built-In VoIP Channel	8 (Built-in) / 128 (By VoIP board)			
Physical Characteristics	SL2100 Chassis Dimensions	H 92.9mm X W 435mm X D 330mm			
	Empty Chassis Weight	2.2 Kg			
Power Consumption	SL2100 Chassis Power Rating	Input 100V-120V/220V/230V/240V 50/60Hz 1.43A 1.25A/0.82A/0.79A/0.76A OR DC-24V 2.86A			
Compliance	EMC	EN55032 Emission, EN55024 Immunity, EN6100 Powering			
	Safety	EN60950-1			
	Transmission and Signaling	TBR3, TBR4, ES203-021, TBR8, TBR38			
Environment	Temperature	0°C-40°C (32F-104F)			
	Humidity	10%-90% (non-condensing)			